

Normalabmessungen für Type 305 STEDL

Bestellnummer	Tragkraft daN	Tischgröße mm	Tischhöhe gesenkt mm	Nutzhub mm	Motorstärke kW	Hubzeit sec.	Bestellnummer	Tragkraft daN	Tischgröße mm	Tischhöhe gesenkt mm	Nutzhub mm	Motorstärke kW	Hubzeit sec
STEDL 3/5-10	3000	5000×1000	300	1200	3,0	40	STEDL 10/5-10	10000	5000×1000	450	1200	5,5	48
STEDL 3/5-15		5000×1500	300	1200	3,0	42	STEDL 10/5-15		5000×1500	450	1200	5,5	52
STEDL 3/5-24		5000×2400	350	1200	3,0	44	STEDL 10/5-24		5000×2400	500	1200	5,5	56
STEDL 3/8-10		8000×1000	300	1600	3,0	45	STEDL 10/8-10		8000×1000	450	1600	5,5	68
STEDL 3/8-15		8000×1500	300	1600	3,0	47	STEDL 10/8-15		8000×1500	450	1600	5,5	71
STEDL 3/8-24		8000×2400	350	1600	3,0	49	STEDL 10/8-24		8000×2400	500	1600	5,5	77
STEDL 3/12-10		12000×1000	300	1600	3,0	54	STEDL 10/12-10		12000×1000	450	1600	5,5	62
STEDL 3/12-15		12000×1500	300	1600	3,0	56	STEDL 10/12-15		12000×1500	450	1600	5,5	67
STEDL 3/12-24		12000×2400	350	1600	3,0	60	STEDL 10/12-24		12000×2400	500	1600	5,5	73
STEDL 5/5-10	5000	5000×1000	350	1200	4,0	45	STEDL 15/5-10	15000	5000×1000	500	1200	Antrieb entsprechend örtlichen Einsatzbedingungen	
STEDL 5/5-15		5000×1500	350	1200	4,0	48	STEDL 15/5-15		5000×1500	500	1200		
STEDL 5/5-24		5000×2400	400	1200	4,0	52	STEDL 15/5-24		5000×2400	550	1200		
STEDL 5/8-10		8000×1000	350	1600	4,0	53	STEDL 15/8-10		8000×1000	500	1600		
STEDL 5/8-15		8000×1500	350	1600	4,0	56	STEDL 15/8-15		8000×1500	500	1600		
STEDL 5/8-24		8000×2400	400	1600	4,0	58	STEDL 15/8-24		8000×2400	550	1600		
STEDL 5/12-10		12000×1000	350	1600	4,0	64	STEDL 15/12-10		12000×1000	500	1600		
STEDL 5/12-15		12000×1500	350	1600	4,0	67	STEDL 15/12-15		12000×1500	500	1600		
STEDL 5/12-24		12000×2400	400	1600	4,0	73	STEDL 15/12-24		12000×2400	550	1600		
STEDL 8/5-10	8000	5000×1000	400	1200	4,0	45	STEDL 20/5-10	20000	5000×1000	600	1200		
STEDL 8/5-15		5000×1500	400	1200	4,0	48	STEDL 20/5-15		5000×1500	600	1200		
STEDL 8/5-24		5000×2400	450	1200	4,0	51	STEDL 20/5-24		5000×2400	700	1200		
STEDL 8/8-10		8000×1000	400	1600	4,0	72	STEDL 20/8-10		8000×1000	600	1600		
STEDL 8/8-15		8000×1500	400	1600	4,0	75	STEDL 20/8-15		8000×1500	600	1600		
STEDL 8/8-24		8000×2400	450	1600	4,0	84	STEDL 20/8-24		8000×2400	750	1600		
STEDL 8/12-10		12000×1000	400	1600	5,5	55	STEDL 20/12-10		12000×1000	600	1600		
STEDL 8/12-15		12000×1500	400	1600	5,5	58	STEDL 20/12-15		12000×1500	600	1600		
STEDL 8/12-24		12000×2400	450	1600	5,5	63	STEDL 20/12-24		12000×2400	750	1600		

Bei Plattformlängen über 5000 mm sind unter bestimmten Voraussetzungen größere Hubhöhen möglich. Bitte Rückfrage.